




100%
MADE IN ITALY



LINDHAUS®

QUALITY CLEANING EQUIPMENT

P R O F E S S I O N A L L I N E



LW46 HYBRID
LW46 ELECTRIC
LW46 DUAL CORE



LW46 Hybrid LW46 Electric LW46 DUAL CORE

Hybrid scrubber drier for medium and large surfaces

STRENGTHS

- Design, technology and construction 100% made in Italy
- **Use with battery and cord** for extended working time
- High efficiency **Rotafil** motors for the longest running time
- Maneuverable and light, just guide it and it goes by itself!
- Removable water tanks on the body frame
- The world's lowest base housing profile: 230 mm (9 in)
- **Superior working capacity: 1500 sqm/h (16150 sqft/h)**
- Scrubs + dries wall to wall + front
- Dries perfectly on turns thanks to the easy glide suction nozzle
- Quick brush roller and squeegee replacement **without tools**
- The body frame turns to fold the machine for transport in a vehicle
- Light weight and low noise level



LW46 Hybrid/Electric



LW46 DUAL CORE



APPLICATION FIELDS

LW46 Hybrid can operate on **any type of hard floor** with spaces from 200 to 2000 sqm (2000 to 20000 sqft). **LW46** is ideal for a wide range of environments: car and motorcycle showrooms, churches and museums, dance schools and sports halls, kindergartens, schools, medical centers and hospitals, airports and railway stations, supermarkets and shopping malls, restaurants and fast food, production activities in general, poolside, sport centers and many others.

MAINTENANCE WITHOUT TOOLS

The easy glide suction nozzle turns in the opposite direction of the machine in order to thoroughly pick up the water. It can be removed **without tools** and the squeegee can be rotate for 4 side use resulting in maximum cost reduction. The machine has one high speed brush roller (1200 RPM) exposed in front for baseboard cleaning. It is **dynamically balanced** and can be replaced **in a few seconds without tools**. The brush pressure is adjustable.

REMOVABLE WATER TANKS MOUNTED ON THE BODY FRAME

The light blue solution tank is equipped with measuring cap. The front recovery tank is equipped with a float system and a motor protection filter. All filters are **antiseptic treated** to eliminate bacteria's, fungi's and dust mites on contact. The body frame is easily **adjustable 160°** for maximum operator manoeuvrability. It allow easy access under tables and low furniture and allows the machine to fold for transport in a vehicle.


ON BOARD BATTERY CHARGER

The machine is **100% Hybrid** and it works with battery or a power supply with a 15 m (50 ft) cord on board. The recharging time after a complete discharge is reduced to **3 hours** instead of the 12 hours of GEL battery. On down time it is possible to recharge the batteries without waiting the complete discharge.



NEW GENERATION BATTERY

The two cylindrical and sealed AGM batteries are made by Optima U.S.A. This new technology allows a much longer discharge time at the same capacity while maintaining the performance. The recharge time is much quicker. The number of recharging cycles is about double compared to the standard GEL batteries and can be recharged as often as you want even with partial discharge. Capable of vibrations, impacts and temperature variations. Air transport is allowed.



Lindhaus has developed a few effective and completely foam free concentrated detergents:

Neutrolux: neutral, self polishing and light scented

Actiplus: degreasing detergent

Actistrong: aggressive degreaser



HIGH EFFICIENCY MOTORS

The **high efficiency dual stage vacuum motor** 24VCC - 360W is made by the parent company **Rotafil** located in Padova - Italy. Very efficient while keeping with the highest performance. The permanent magnet brush motor 24VCC - 150W is also manufactured by **Rotafil**. Both those new motors have been specifically developed for this machine. The maximum power consumption is **only 300W** during the recharge and in the use with cord.

ROLLERS

LW46 Hybrid has no limits when it comes to the perfect cleaning of **any hard surfaces** as: marble, wood, ceramic, resin, quartz etc. The brush pressure is adjustable. A large selection of other brushes or abrasive disks are available to handle any type of job from delicate to difficult.

SPECIAL VERSION: LW46 Hybrid DUAL CORE

- Scrubber Drier and Carpet Cleaner
- All in one Unique High Tech Machine
- Upgraded motors

Standard equipment:

- Carpet brush and nozzle kit
- Floor brush and nozzle kit





TECHNICAL SPECIFICATIONS	LW46 Hybrid	LW46 Electric	LW46 Dual Core
Working width - vacuum mm (in)	520 (20.5)	520 (20.5)	520 (20.5)
Working width - brush mm (in)	460 (18.1)	460 (18.1)	460 (18.1)
Working capacity apx. sqm/h (sqf/h)	1500 (16150)	1000 (10765)	1500 (16150)
Solution tank capacity (lt.)	10	10	10
Recovery tank capacity (lt.)	13	13	13
Brush roller rotation speed (RPM)	1200	1200	1200
Base height mm (in)	230 (9)	230 (9)	230 (9)
Weight on handle full tank kg (lb)	0	0	0
Voltage/Frequency (V/Hz)	24 DC	220-240/50-60	24 DC
Input power (W)	540	900	650
Rotafil high-efficiency vacuum motor (W)	360	600	450
Rotafil top-performance brush motor (W)	150	300	200
Power cord length m (ft)	15 (49.2)	15 (49.2)	15 (49.2)
Water-lift/vacuum mm/H ₂ O (in/H ₂ O)	1250 (49.2)	1800 (71)	1450 (57.1)
Air flow lt./sec. (CFM)	35 (74.1)	40 (84.7)	38 (80.5)
Battery charger (V/Hz)	100-240/50-60	-	100-240/50-60
Run-time - fully charged battery (min.)	90	-	45
Battery recharging time (min.)	180	-	180
Electronic overload control	Standard	Standard	Standard
Electronic pump control	Standard	Standard	Standard
Water dosing	Pump	Pump	Pump
Protection class	IPX4	IPX4	IPX4
Noise level (dbA)	68	69	69
Total net weight kg (lb)	60.4 (133)	43 (95)	60,4
Dimensions mm (in)	505x600x1200 (19.9x23.6x47.2)		



HEADQUARTERS • LINDHAUS SRL
Via Belgio, 22 Z.I. 35127 • Padova, ITALY
tel. +39 049 8700307 • fax +39 049 8700605
vacuum@lindhaus.it • www.lindhaus.it

LINDHAUS USA
Minneapolis • Minnesota USA
tel. 800 498 7526 • Fax 952 707 1134
info@lindhaus.com • www.lindhaususa.com

DEALER STAMP

The company Lindhaus srl reserves its right to make any modifications without any prior notice.